

# OPEN MOTORCYCLE TRAILERS

5x8 & 6.5x10



## 5x8 & 6.5x10

### STANDARD FEATURES

- > All Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > 3500# Straight-Pull Style Coupler w/ 2" Ball
- > (2) 5000# Safety Chains
- > Dexter Torsion Ride Axles
- > Easy Removable Aluminum Fenders
- > Extruded Aluminum Decking
- > Removable 18" Aluminum Stone Guard
- > HD Aluminum Pull-Out Ramp (36"x60") For 5x8 Trailer
- > HD Aluminum Pull Out Ramp (46"x60") For 6.5x10 Trailer
- > (2) Surface-Mounted Aluminum Wheel Chocks (Gusseted, Fits Up to 7" Wide Tire)
- > Recessed LED Marker Lights
- > Adjustable Perimeter Track for Easy Install Options
- > 5-Year Limited Warranty

### STANDARD SPECIFICATIONS

TRAILER MODEL	5X8	6.5X10
Model Number	COMC5x8-2.0	COMC6.5x10-2.0
Deck (WxL)	56"x96"	76"x120"
Overall (WxL)	82"x170"	102"x204"
Deck Height	16"	18"
Hitch Height	13"	14"
Axle(s) - Qty/Rating	1-2200# Idler	1-3500# Idler
Wheels	13" Aluminum	14" Aluminum
Tires	175/80R13	205/75R14
GVWR	2200#	2990#
Curb Weight	400#	550#
Payload	1800#	2440#
Easy Adjust D-Rings	4	8
Wheel Jack	1200#	1500#
Power Connection	4-Way Flat	4-Way Flat

### OPTIONS & ACCESSORIES

TIRE/WHEEL ASSEMBLIES & ACCESSORIES
Spare 13" Aluminum Wheel w/ 175/80R13 Tire
Spare 14" Aluminum Wheel w/ 205/75R14 Tire
Upgrade to 14" Aluminum (Radial Ply; From 13" Aluminum Wheels)
Upgrade to 15" Aluminum (Radial Ply; From 14" Aluminum Wheels)
RAMP OPTIONS
Upgrade to Full Width Ramp
Upgrade to Rear Ramp (Replaces Stowaway Ramp)
TIE-DOWN OPTIONS
Light Duty Surface-Mounted D-Ring (Installed)

ACCESSORIES
Stabilizer Jacks (Installed; Pair)
EASY INSTALL/ADJUST OPTIONS
Easy Install/Adjust Spare Tire Mount
Easy Install/Adjust Stake Pocket Kit: Includes (4) Stake Pockets w/ Hardware
Easy Install/Adjust D-Ring Kit: Includes (4) 2,000lb D-Rings and Hardware
Easy Install/Adjust D-Ring
Easy Install/Adjust Drop Down Stabilizer Jacks (Pair)



# RAMP CAPACITY BY MODEL

RAMP TYPE	APPLICABLE MODELS	CAPACITY
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes); RA 2.0 (All Sizes); RW 2.0 (All Sizes); FA 2.0 (All Sizes); Landscape (LS) 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down, Bi-Fold)	SSR (Optional, All Sizes); RA 2.0 (Optional, All Sizes); RW 2.0 (Optional, All Sizes); FA 2.0 (Optional, All Sizes); Landscape (LS) 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (PAIR)
Deckover Equipment Trailer Ramps 14K (Fold-Down)	(All Sizes)	5000# (PAIR)
UHD Ramps (Fold-Down)	(All Sizes)	4000# (PAIR)
UHD Ramps 14K (Fold-Down)	(All Sizes)	5000# (PAIR)
Dump Trailer Ramps (Side-Stow, Optional)	(All Sizes)	4000# (PAIR)
ATV Ramps (83" Wide, Side-Stow)	(All Sizes)	1200# (PAIR)
ATV Ramps (84" or 9" Wide, Side-Stow)	(All Sizes)	750# (PAIR)
Open Motorcycle Ramp (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down, Bi-Fold)	U-SLINGSHOT	1500#
Open Car Hauler 2.0 Ramps (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler 2.0 Ramps 10K (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler Standard (Stow)	(All Sizes)	4000# (PAIR)
Open Snow Ramp (Rear-Stow)	SnoPro Drive On/Off	750#
Sport Deck (Rear-Stow, Telescoping Ramps)	SSD	1000#
Enclosed Cargo Ramp (4', 5', 6' Wide)	(All Sizes)	1500#
Enclosed Cargo Ramp (7' & 7.5' Wide)	(All Sizes)	1500#
Enclosed Cargo Ramp (8.5' Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle Ramp (7' Wide)	(All Sizes)	1500#
Enclosed Car Hauler Ramp (8.5' Wide)	(All Sizes)	4000#
Enclosed Gooseneck Ramp (8.5' Wide, Rear)	(All Sizes)	4000#
Enclosed Gooseneck Ramp (8.5' Wide, Side, Optional)	(All Sizes)	1200#
Enclosed Snowmobile Ramp (7', 7.5', 101" Wide, Rear)	(All Sizes)	1500#
Enclosed Snowmobile Ramp (7', 7.5', 101" Wide, Front)	(All Sizes)	1200#
Enclosed Snowmobile Ramp (Hybrid, Rear)	(All Sizes)	1500#



# TONGUE EXTENSION BY MODEL

TRAILER TYPE	ALLOWABLE EXTENSION	ADDITIONAL REQUIREMENTS	ITEM NUMBER	DESCRIPTION
Enclosed Cargo (4' & 5' Wide)	N/A	Frame Upgrade Required; Consult Engineering	N/A	N/A
Enclosed Cargo (6', 7', 7.5' Wide)	12"	Economy Models Require Center Beam Upgrade	TONGUE12EXT	12" Extended Tongue (For 3k Tandem Axle Enclosed with 2"x5" Frame); Includes Center Beam Upgrade; Not Available With All Sport or Snow Trailers.
Enclosed Cargo (8.5' Wide, Premium)	12" (16" w/ Upgrade)	Min. 6" Frame for 16" Tongue Extension; Upgrade May Be Required	TONGUE12EXT	12" Extended Tongue (For 3k Tandem Axle Enclosed with 2"x5" Frame) Includes Center Beam Upgrade; Not Available With All Sport or Snow Trailers.
Enclosed Motorcycle (7' Wide)	12"	N/A	TONGUE12EXT	12" Extended Tongue (For 3k Tandem Axle Enclosed with 2"x5" Frame); Includes Center Beam Upgrade; Not Available With All Sport or Snow Trailers.
Enclosed Car Hauler (8.5' Wide, Premium)	16"	N/A	TONGUE16EXTCH	16" Extended Tongue (For 5k Tandem Axle Enclosed w/2"x6" Frame or Larger); Not Available With All Sport or Snow Trailers.
Enclosed Car Hauler - All Sport (8.5' Wide)	N/A	Extended Tongue Incompatible With Front Ramp	N/A	N/A
Enclosed Snowmobile (7' & 7.5' Wide)	N/A	Extended Tongue Incompatible With Front Ramp	N/A	N/A
Enclosed Snowmobile (101" Wide)	10"	Requires 3"x5" Tongue Upgrade w/Straight-Pull Coupler	TBD	TBD

\*\*Please note that all 5k tandem trailers w/ extended tongues require a minimum of 6" base frame, regardless of brand/model