

OPEN UTILITY FA 2.0 TANDEM AXLE

12', 14', 14' 5K



12', 14', 14' 5K

STANDARD FEATURES

- › All-Aluminum Construction
- › 2"x5" Subframe Tubing
- › 24" O/C Floor Crossmembers
- › 1500# Wheel Jack
- › Torsion Ride Braked Axles
- › Adjustable Perimeter Track for Easy Install Options
- › Integrated Rear Ramp with Beveled Edge
- › 4-Piece Extruded Hinge System
- › 7-Way Round Power Connection
- › Extruded Aluminum Decking
- › Fixed 2"x2" Aluminum Side Rail Kit
- › Easy Removable Aluminum Fenders
- › 2" Straight Pull Coupler
- › (2) 7800# Safety Chains
- › 5-Year Limited Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	6.5X14	6.5X16	6.5X18	6.5X20
Model Number	U6.5x14FA-TA-2.0	U6.5x16FA-TA-2.0	U6.5x18FA-TA-2.0	U6.5x20FA-TA-2.0
Deck (WxL)	76"x169"	76"x192"	76"x215"	76"x239"
Overall (WxL)	102"x223"	102"x246"	102"x269"	102"x292"
Deck Height	17"	17"	17"	17"
Hitch Height	14"	14"	14"	14"
Axle(s) - Qty/Rating	2-3500#	2-3500#	2-3500#	2-3500#
Wheels	14" Aluminum	14" Aluminum	14" Aluminum	14" Aluminum
Tires	205/75R14	205/75R14	205/75R14	205/75R14
Tongue	Triple-Tube	Triple-Tube	Triple-Tube	Triple-Tube
GVWR	7000#	7000#	7000#	7000#
Curb Weight	1134#	1168#	1202#	1236#
Payload	5866#	5832#	5798#	5764#
Power Connection	7-Way Round	7-Way Round	7-Way Round	7-Way Round

OPTIONS & ACCESSORIES

RAMP OPTIONS

- Upgrade to Bi-Fold Rear Ramp
- Upgrade to Slide Out 4000# Ramp Kit (Replaces Fold Down Ramp; Includes U-Channel)

TIRE/WHEEL ASSEMBLIES & ACCESSORIES

- Spare 14" Aluminum Wheel w/ 205/75R14 Tire
- Spare 15" Aluminum Wheel w/ 205/75R15 Tire
- Downgrade to Silver Mods From Aluminum Rims
- Upgrade to 15" Aluminum (Radial Ply; From 14" Aluminum Wheels)

TIE-DOWN OPTIONS

- 5000# Recessed Heavy Duty D-Ring w/Backing Plate (Installed)
- Stainless Steel 6000# Recessed Swivel D-Ring w/Backing Plate (Installed)

EASY INSTALL/ADJUST OPTIONS

- Easy Install/Adjust Spare Tire Mount (RA or FA 2.0)
- Easy Install/Adjust Stake Pocket Kit (RA or FA 2.0): (4) Stake Pockets w/ Hardware
- Easy Install/Adjust D-Ring Kit (RA or FA 2.0): Includes (4) 2,000lb D-Rings & Hardware
- Easy Install/Adjust D-Ring (RA or FA 2.0)
- Easy Install/Adjust Drop-Down Stabilizer Jacks (Pair; RA or FA 2.0)



RAMP CAPACITY BY MODEL

RAMP TYPE	APPLICABLE MODELS	CAPACITY
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes); RA 2.0 (All Sizes); RW 2.0 (All Sizes); FA 2.0 (All Sizes); Landscape (LS) 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down, Bi-Fold)	SSR (Optional, All Sizes); RA 2.0 (Optional, All Sizes); RW 2.0 (Optional, All Sizes); FA 2.0 (Optional, All Sizes); Landscape (LS) 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (PAIR)
Deckover Equipment Trailer Ramps 14K (Fold-Down)	(All Sizes)	5000# (PAIR)
UHD Ramps (Fold-Down)	(All Sizes)	4000# (PAIR)
UHD Ramps 14K (Fold-Down)	(All Sizes)	5000# (PAIR)
Dump Trailer Ramps (Side-Stow, Optional)	(All Sizes)	4000# (PAIR)
ATV Ramps (83" Wide, Side-Stow)	(All Sizes)	1200# (PAIR)
ATV Ramps (84" or 9" Wide, Side-Stow)	(All Sizes)	750# (PAIR)
Open Motorcycle Ramp (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down, Bi-Fold)	U-SLINGSHOT	1500#
Open Car Hauler 2.0 Ramps (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler 2.0 Ramps 10K (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler Standard (Stow)	(All Sizes)	4000# (PAIR)
Open Snow Ramp (Rear-Stow)	SnoPro Drive On/Off	750#
Sport Deck (Rear-Stow, Telescoping Ramps)	SSD	1000#
Enclosed Cargo Ramp (4', 5', 6' Wide)	(All Sizes)	1500#
Enclosed Cargo Ramp (7' & 7.5' Wide)	(All Sizes)	1500#
Enclosed Cargo Ramp (8.5' Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle Ramp (7' Wide)	(All Sizes)	1500#
Enclosed Car Hauler Ramp (8.5' Wide)	(All Sizes)	4000#
Enclosed Gooseneck Ramp (8.5' Wide, Rear)	(All Sizes)	4000#
Enclosed Gooseneck Ramp (8.5' Wide, Side, Optional)	(All Sizes)	1200#
Enclosed Snowmobile Ramp (7', 7.5', 101" Wide, Rear)	(All Sizes)	1500#
Enclosed Snowmobile Ramp (7', 7.5', 101" Wide, Front)	(All Sizes)	1200#
Enclosed Snowmobile Ramp (Hybrid, Rear)	(All Sizes)	1500#