

OPEN UTILITY FA TILTING 2.0

12', 14', 14' 5K



12', 14', 14' 5K

STANDARD FEATURES

- > All Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > (2) 5000# Safety Chains
- > 6000# Coupler w/2" Ball
- > Torsion Ride Idler Axle
- > Easy Removable Aluminum Fenders
- > Extruded Aluminum Decking
- > Tilt System w/Hydraulic Dampener
- > Fixed 2"x2" Aluminum Side Rail Kit
- > Exterior LED Lights
- > Adjustable Perimeter Track for Easy Install Options
- > 5-Year Limited Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	6.5X12	6.5X14	6.5X14 5K
Model Number	U6.5x12FA-TILT-2.0	U6.5x14FA-TILT-2.0	U6.5x14FA-TILT-2.0-5K
Deck (WxL)	76"x146"	76"x169"	76"x169"
Overall (WxL)	102"x200"	102"x223"	102"x223"
Deck Height	17"	17"	17"
Hitch Height	14"	14"	14"
Axle(s) - Qty/Rating	1-3500#	1-3500#	1-5200# Braked
Wheels	14" Aluminum	14" Aluminum	15" Aluminum
Tires	205/75R14	205/75R14	225/75R15
Tongue	Triple-Tube	Triple-Tube	Triple-Tube
GVWR	2990#	2990#	4400#
Curb Weight	480#	560#	754#
Payload	2510#	2430#	3646#
Power Connection	4-Way Flat	4-Way Flat	4-Way Flat

OPTIONS & ACCESSORIES

RAIL KIT OPTIONS (2.0) MODELS
FR Series Easy Install 10" Solid Aluminum Rail Kit (6.5x12) (FA 2.0)
FR Series Easy Install 10" Solid Aluminum Rail Kit (6.5x14) (FA 2.0)
FR Series Easy Install 17" Slatted Aluminum Rail Kit w/Solid Front (6.5x12) (FA 2.0)
FR Series Easy Install 17" Slatted Aluminum Rail Kit w/Solid Front (6.5x14) (FA 2.0)
TIRE/WHEEL ASSEMBLIES & ACCESSORIES
Spare 14" Aluminum Wheel w/ 205/75R14 Tire
Spare 15" Aluminum Wheel w/ 205/75R15 Tire
Spare 15" Aluminum Wheel w/ 225/75R15 Tire (6-Lug)
Downgrade to Silver Mods From Aluminum Rims
Upgrade to 15" Aluminum (Radial Ply; From 14" Aluminum Wheels)

EASY INSTALL/ADJUST OPTIONS
Easy Install/Adjust Spare Tire Mount (RA or FA 2.0)
Easy Install/Adjust Stake Pocket Kit (RA or FA 2.0): (4) Stake Pockets w/Hardware
Easy Install/Adjust D-Ring Kit (RA or FA 2.0): (4) 2,000lb D-Rings and Hardware
Easy Install/Adjust D-Ring (RA or FA 2.0)
Easy Install/Adjust Drop-Down Stabilizer Jacks (RA or FA 2.0)



RAMP CAPACITY BY MODEL

RAMP TYPE	APPLICABLE MODELS	CAPACITY
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes); RA 2.0 (All Sizes); RW 2.0 (All Sizes); FA 2.0 (All Sizes); Landscape (LS) 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down, Bi-Fold)	SSR (Optional, All Sizes); RA 2.0 (Optional, All Sizes); RW 2.0 (Optional, All Sizes); FA 2.0 (Optional, All Sizes); Landscape (LS) 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (PAIR)
Deckover Equipment Trailer Ramps 14K (Fold-Down)	(All Sizes)	5000# (PAIR)
UHD Ramps (Fold-Down)	(All Sizes)	4000# (PAIR)
UHD Ramps 14K (Fold-Down)	(All Sizes)	5000# (PAIR)
Dump Trailer Ramps (Side-Stow, Optional)	(All Sizes)	4000# (PAIR)
ATV Ramps (83" Wide, Side-Stow)	(All Sizes)	1200# (PAIR)
ATV Ramps (84" or 9" Wide, Side-Stow)	(All Sizes)	750# (PAIR)
Open Motorcycle Ramp (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down, Bi-Fold)	U-SLINGSHOT	1500#
Open Car Hauler 2.0 Ramps (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler 2.0 Ramps 10K (Stow)	(All Sizes)	4000# (PAIR)
Open Car Hauler Standard (Stow)	(All Sizes)	4000# (PAIR)
Open Snow Ramp (Rear-Stow)	SnoPro Drive On/Off	750#
Sport Deck (Rear-Stow, Telescoping Ramps)	SSD	1000#
Enclosed Cargo Ramp (4', 5', 6' Wide)	(All Sizes)	1500#
Enclosed Cargo Ramp (7' & 7.5' Wide)	(All Sizes)	1500#
Enclosed Cargo Ramp (8.5' Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle Ramp (7' Wide)	(All Sizes)	1500#
Enclosed Car Hauler Ramp (8.5' Wide)	(All Sizes)	4000#
Enclosed Gooseneck Ramp (8.5' Wide, Rear)	(All Sizes)	4000#
Enclosed Gooseneck Ramp (8.5' Wide, Side, Optional)	(All Sizes)	1200#
Enclosed Snowmobile Ramp (7', 7.5', 101" Wide, Rear)	(All Sizes)	1500#
Enclosed Snowmobile Ramp (7', 7.5', 101" Wide, Front)	(All Sizes)	1200#
Enclosed Snowmobile Ramp (Hybrid, Rear)	(All Sizes)	1500#