

RAFT TRAILERS

10' & 12'



10' & 12'

STANDARD FEATURES

- > All Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > 6000# Straight Coupler w/ 2" Ball
- > (2) 5000# Safety Chains
- > Dexter Torsion Ride Axles
- > 5/4" Pressure Treated Decking
- > Rear Roller w/Bearings
- > Manual Winch w/24" Post
- > (5) Tie-Down Points Per Side
- > (2) Front Tie-Down Points
- > Recessed LED Marker Lights
- > Limited 4-Year Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	10' RAFT	12' RAFT
Model Number	URFT84x10	URFT84x12
Deck (WxL)	84"x10'	84"x12'
Overall (WxL)	84"x14'	84"x16'
Deck Height	26"	26"
Hitch Height	21"	21"
Axle(s) - Qty/Rating	1-2200# Idler	1-2200# Idler
Wheels	13" Silver Mods	13" Silver Mods
Tires	175/80R13	175/80R13
GVWR	2200#	2200#
Curb Weight	540#	590#
Payload	1660#	1610#
Power Connection	4-Way Flat	4-Way Flat

OPTIONS & ACCESSORIES (Expanded list of available options can be found in MES option Section)

TIRE/WHEEL ASSEMBLIES & ACCESSORIES
Spare 13" Silver Mod Wheel w/ 175/80R13 Tire
Upgrade to 13" Aluminum (Radial; From 13" Silver Mod Wheels)
Bolt-On Spare Tire Carrier (Tongue-Mounted)
CONSTRUCTION OPTIONS
Tilt Bed Option (Pin System)
Anti-Rattle Tilt Bed Option
Upgrade to 36" Winch Post (Replaces 24" Winch Post)

FLOORING OPTIONS
Upgrade to 3/4" Quad Ply Decking (Non-Skid Surface, FRP Backer; PBF)
TIE DOWN OPTIONS
D-Rings for Raft Trailer (Bolt-On)
Welded Side Tie-Down Ring
Light Duty Surface-Mounted D-Ring (Installed)
ACCESSORIES
Add 1200# Tongue-Mounted Wheel Jack