

14', 16', 18', 20'

STANDARD FEATURES

- > All-Aluminum Construction
- > 2"x5" Subframe Tubing
- > 24" O/C Floor Crossmembers
- > 1500# Wheel Jack
- > Torsion Ride Braked Axles
- Adjustable Perimeter Track for Easy Install Options
- > Integrated Rear Ramp with Beveled Edge
- > 4-Piece Extruded Hinge System
- > 7-Way Round Power Connection
- > Extruded Aluminum Decking
- > Fixed 2"x2" Aluminum Side Rail Kit
- > Easy Removable Aluminum Fenders
- > 2" Straight Pull Coupler
- > (2) 7800# Safety Chains
- > 5-Year Limited Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	6.5X14	6.5X16	6.5X18	6.5X20
Model Number	HU6.5x14FA-TA-2.0	HU6.5x16FA-TA-2.0	HU6.5x18FA-TA-2.0	HU6.5x20FA-TA-2.0
Deck (WxL)	76"x169"	76"x192"	76"x215"	76"x239"
Overall (WxL)	102"x223"	102"x246"	102"x269"	102"x292"
Deck Height	17"	17"	17"	17"
Hitch Height	14"	14"	14"	14"
Axle(s) - Qty/Rating	2-3500#	2-3500#	2-3500#	2-3500#
Wheels	14" Aluminum	14" Aluminum	14" Aluminum	14" Aluminum
Tires	205/75R14	205/75R14	205/75R14	205/75R14
Tongue	Triple-Tube	Triple-Tube	Triple-Tube	Triple-Tube
GVWR	7000#	7000#	7000#	7000#
Curb Weight	1134#	1168#	1202#	1236#
Payload	5866#	5832#	5798#	5764#
Power Connection	7-Way Round	7-Way Round	7-Way Round	7-Way Round

OPTIONS & ACCESSORIES

RAMP OPTIONS

Upgrade to Bi-Fold Rear Ramp

Upgrade to Slide-Out 4000# Ramp Kit (Replaces Fold Down Ramp; Includes U-Channel)

TIRE/WHEEL ASSEMBLIES & ACCESSORIES

Spare 14" Aluminum Wheel w/ 205/75R14 Tire

Spare 15" Aluminum Wheel w/ 205/75R15 Tire

Downgrade to Silver Mods From Aluminum Rims

Upgrade to 15" Aluminum (Radial Ply; From 14" Aluminum Wheels)

TIE-DOWN OPTIONS

5000# Recessed Heavy Duty D-Ring w/Backing Plate (Installed)

Stainless Steel 6000# Recessed Swivel D-Ring w/Backing Plate (Installed)

EASY INSTALL/ADJUST OPTIONS

Easy Install/Adjust Spare Tire Mount

Easy Install/Adjust Stake Pocket Kit: Includes (4) Stake Pockets w/Hardware

Easy Install/Adjust D-Ring Kit: Includes (4) 2,000lb D-Rings and Hardware

Easy Install/Adjust D-Ring

Easy Install/Adjust Drop-Down Stabilizer Jacks (Pair)





RAMP CAPACITY BY MODEL

Ramp Type	Applicaple Models	Capcity
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes), AR 2.0 (All Sizes), WR 2.0 (All Sizes), FA 2.0 (All Sizes), Landscape 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down Bi-Fold)	SSR (Optional, All Sizes), AR 2.0 (Optional, All Sizes), WR 2.0 (Optional, All Sizes), FA 2.0 (Optional, All Sizes), Landscape 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (Pair)
Deckover Equipment Trailer Ramps 14K (Fold-Down)	(All Sizes)	5000# (Pair)
Patriot Ramps (Fold-Down)	Stowaway 6' Aluminum Ramps	4000# (Pair)
Patriot Ramps 14K (Fold-Down)	(All Sizes)	5000# (Pair)
Dump Trailers (Side-Stow, Optional)	(All Sizes)	4000# (Pair)
ATV (83" Wide, Side-Stow)	(All Sizes)	1200# (Pair)
ATV (88" Wide, Side-Stow)	(All Sizes)	750# (Pair)
Open Motorcycle (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down Bi-Fold)	HU-SLINGSH0T	1500#
Open Car Hauler 2.0 (Stow)	(All Sizes)	4000# (Pair)
Open Car Hauler 2.0-10K (Stow)	(All Sizes)	4000# (Pair)
Open Car Hauler Standard (Stow)	(All Sizes)	4000# (Pair)
Open Snow (Rear Stow)	HFS	750#
Sport Deck (Rear Stow, Telescoping)	HFS	1000#
Enclosed Cargo (4', 5', 6' Wide)	(All Sizes)	1500#
Enclosed Cargo (7', 7.5' Wide)	(All Sizes)	1500#
Enclosed Cargo (8.5' Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle (7' Wide)	(All Sizes)	1500#
Enclosed Car Hauler (8.5' Wide)	(All Sizes)	4000#
Enclosed Gooseneck (8.5' Wide, Rear)	(All Sizes)	4000#
Enclosed Gooseneck (8.5' Wide, Side, Optional)	(All Sizes)	1200#
Enclosed Snowmobile (7', 7.5', 101" Wide, Rear)	(All Sizes)	1500#
Enclosed Snowmobile (7', 7.5', 101" Wide, Front)	(All Sizes)	1200#
Enclosed Snowmobile (Crossover, Rear)	(All Sizes)	1500#

