

STANDARD FEATURES

- > All-Aluminum Construction
- > 24" 0/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > 3500# Wishbone Style Coupler w/2" Ball
- > (2) 5000# Safety Chains
- > Leaf Spring Axles
- > 1200# Wheel Jack
- > 5/4" Pressure Treated Decking
- > Custom Angle Side Rails for Low Profile Side Loading
- > 4-Way Flat Power Connection (7-Way Connection for Braked Models)
- Rear & Front Stowing Removable 8' Ramps
- > Recessed Rubber Mounted LED Lights
- > Limited 1-Year Warranty

STANDARD SPECIFICATIONS

Trailer Model	ATV Side/Rear Load 83"x14'
Model Number	PATV83x14
Deck (WxL)	7'x14'
Overall (WxL)	8'x18'
Deck Height	TBD
Hitch Height	18"
Decking	5/4" PT
Surface Mount D-Rings	Optional
Axle(s) - Qty/Rating	1-3500#
Wheels	15" Silver Mods
Tires	205/75R15
GVWR	2990#
Curb Weight	904#
Payload	2086#
Wheel Jack	Yes

OPTIONS & ACCESSORIES (Expanded list of available options can be found in MES option Section)

CEXPANDED (EXPANDED LIST OF AVAILABLE OF AVAILABLE OF THE OFFICE OF AVAILABLE OF THE OFFICE OF AVAILABLE OF THE OFFICE OF AVAILABLE OF			
FLOORING OPTIONS	TIE DOWN OPTIONS		
Upgrade to Extruded Aluminum Floor (PBF)	Light Duty Surface-Mounted D-Ring (Installed)		
TIRE/WHEEL ASSEMBLIES & ACCESSORIES	5000# Recessed Heavy Duty D-Ring w/Backing Plate (Installed)		
Spare 15" Silver Mod Wheel w/ 205/75R15 Tire	ACCESSORIES		
Spare 15" Aluminum Wheel w/ 205/75R15 Tire	1200# Wheel Jack		
Upgrade to 15" Aluminum (Radial; From 15" Silver Mod Radial Wheels)			
Bolt-On Spare Tire Carrier (Tongue-Mounted)			

