

OPEN FA 2.0 TILTING UTILITY TRAILERS

6.5'x12' & 6.5'x14'

POLARIS
TRAILERS



6.5'x12' & 6.5'x14'

STANDARD FEATURES

- > All-Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > (2) 5000# Safety Chains
- > 6000# Coupler w/2" Ball
- > Torsion Ride Idler Axle
- > Adjustable Perimeter Track for Easy Install Options
- > Extruded Aluminum Decking
- > Tilt Bed With Hydraulic Dampener System
- > Fixed 2"x2" Aluminum Side Rail Kit
- > Exterior LED Lights
- > 4-Way Flat Power Connection
- > EASY Removable Aluminum Fenders
- > 5-Year Limited Warranty

STANDARD SPECIFICATIONS

Trailer Model	Fixed Rail Tilt 6.5x12	Fixed Rail Tilt 6.5x14
Model Number	PU6.5x12FA-TILT-2.0	PU6.5x14FA-TILT-2.0
Deck (WxL)	76"x146"	76"x169"
Overall (WxL)	102"x200"	102"x223"
Deck Height	17"	17"
Hitch Height	14"	14"
Axle(s) - Qty/Rating	1-3500#	1-3500#
Wheels	14" Aluminum	14" Aluminum
Tires	205/75R14	205/75R14
Tongue	Triple - Tube	Triple - Tube
GVWR	2990#	2990#
Curb Weight	480#	560#
Payload	2510#	2430#

OPTIONS & ACCESSORIES

RAIL KIT OPTIONS (2.0) MODELS

- FR Series Easy Install 10" Solid Aluminum Rail Kit (6.5x12)
- FR Series Easy Install 10" Solid Aluminum Rail Kit (6.5x14)
- FR Series Easy Install 17" Slatted Aluminum Rail Kit w/Solid Front (6.5x12)
- FR Series Easy Install 17" Slatted Aluminum Rail Kit w/Solid Front (6.5x14)

EASY INSTALL/ADJUST OPTIONS

- Easy Install/Adjust Spare Tire Mount
- Easy Install/Adjust Stake Pocket Kit: (4) Stake Pockets w/Hardware
- Easy Install/Adjust D-Ring Kit :(4) 2,000lb D-Rings & Hardware

Easy Install/Adjust Drop-Down Stabilizer Jacks (Pair)

TIRE/WHEEL ASSEMBLIES & ACCESSORIES

- Spare 14" Aluminum Wheel w/205/75R14 Tire
- Spare 15" Silver Mod Wheel w/205/75R15 Tire
- Spare 15" Aluminum Wheel w/205/75R15 Tire
- Upgrade to 15" Aluminum (Radial Ply; From 14" Aluminum Wheels)

RAMP TYPE	APPLICABLE MODELS	CAPACITY
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes); AR 2.0 (All Sizes); WR 2.0 (All Sizes); FA 2.0 (All Sizes); Landscape (LS) 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down, Bi-Fold)	SSR (Optional, All Sizes); AR 2.0 (Optional, All Sizes); WR 2.0 (Optional, All Sizes); FA 2.0 (Optional, All Sizes); Landscape (LS) 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (Pair)
Deckover Equipment Trailer Ramps 14K (Fold-Down)	(All Sizes)	5000# (Pair)
Patriot Ramps (Fold-Down)	(All Sizes)	4000# (Pair)
Patriot Ramps 14K (Fold-Down)	(All Sizes)	5000# (Pair)
Dump Trailers (Side-Stow, Optional)	(All Sizes)	4000# (Pair)
ATV (83-Wide, Side-Stow)	(All Sizes)	1200# (Pair)
ATV (88-Wide, Side-Stow)	(All Sizes)	750# (Pair)
Open Motorcycle (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down, Bi-Fold)	PU-SLINGSHOT	1500#
Open Car Hauler 2.0 (Stow)	(All Sizes)	4000# (Pair)
Open Car Hauler 2.0-10K (Stow)	(All Sizes)	4000# (Pair)
Open Car Hauler Standard (Stow)	(All Sizes)	4000# (Pair)
Open Snow (Rear-Stow)	PFS	750#
Sport Deck (Rear-Stow, Telescoping)	PSD	1000#
Enclosed Cargo (4, 5, 6-Wide)	(All Sizes)	1500#
Enclosed Cargo (7, 7.5-Wide)	(All Sizes)	1500#
Enclosed Cargo (8.5-Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle (7-Wide)	(All Sizes)	1500#
Enclosed Car Hauler (8.5-Wide)	(All Sizes)	4000#
Enclosed Gooseneck (8.5-Wide, Rear)	(All Sizes)	4000#
Enclosed Gooseneck (8.5-Wide, Side, Optional)	(All Sizes)	1200#
Enclosed Snowmobile (7, 7.5, 101-Wide, Rear)	(All Sizes)	1500#
Enclosed Snowmobile (7, 7.5, 101-Wide, Front)	(All Sizes)	1200#
Enclosed Snowmobile (Crossover, Rear)	(All Sizes)	1500#