

OPEN MOTORCYCLE 2.0 TRAILERS

5'x8' & 6.5'x10'

POLARIS
TRAILERS



5'x8' & 6.5'x10'

STANDARD FEATURES

- > All-Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > 3500# Wishbone Style Coupler w/2" Ball
- > (2) 7500# Safety Chains
- > Torsion Ride Axles
- > Easy Removable Aluminum Fenders
- > Extruded Aluminum Decking
- > HD Aluminum Pull Out Ramp
- > 4-Way Flat Power Connection
- > Removable 18" Aluminum Stone Guard
- > Surface-Mounted Aluminum Wheel Chock (Gusseted; Fits Up to 7" Wide Tire)
- > Recessed LED Marker Lights
- > Adjustable Perimeter Track for Easy Install Options
- > 5-Year Limited Warranty

STANDARD SPECIFICATIONS

Trailer Model	Open Motorcycle 5x8	Open Motorcycle 6.5x10
Model Number	POMC5x8-2.0	POMC6.5x10-2.0
Deck (WxL)	56"x96"	76"x120"
Overall (WxL)	82"x170"	102"x204"
Deck Height	16"	18"
Hitch Height	13"	14"
Axle(s) - Qty/Rating	1- 2200#	1-3500#
Wheels	13" Aluminum	14" Aluminum
Tires	175/80R13	205/75R14
GVWR	2200#	2990#
Curb Weight	400#	550#
Payload	1800#	2440#
D-Rings	4	8
Wheel Jack	1200#	1500#

OPTIONS & ACCESSORIES

TIRE/WHEEL ASSEMBLIES & ACCESSORIES
Spare 13" Aluminum Wheel w/ 175/80R13 Tire
Spare 14" Aluminum Wheel w/ 205/75R14 Tire
Upgrade to 14" Aluminum (Radial Ply; From 13" Aluminum)
Upgrade to 15" Aluminum (Radial Ply; From 14" Aluminum Wheels)
RAMP OPTIONS
Upgrade to Rear Ramp (Replaces Stowaway Ramp)

ACCESSORIES
Large, Lockable Tongue-Mounted Diamond Plate Toolbox (Requires Wishbone Tongue)
EASY INSTALL/ADJUST OPTIONS
Easy Install/Adjust Spare Tire Mount
Easy Install/Adjust Stake Pocket Kit: (4) Stake Pockets w/Hardware
Easy Install/Adjust D-Ring Kit: (4) 2,000lb D-Rings & Hardware
Easy Install/Adjust Drop-Down Stabilizer Jacks (Pair)

RAMP TYPE	APPLICABLE MODELS	CAPACITY
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes); AR 2.0 (All Sizes); WR 2.0 (All Sizes); FA 2.0 (All Sizes); Landscape (LS) 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down, Bi-Fold)	SSR (Optional, All Sizes); AR 2.0 (Optional, All Sizes); WR 2.0 (Optional, All Sizes); FA 2.0 (Optional, All Sizes); Landscape (LS) 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (Pair)
Deckover Equipment Trailer Ramps 14K (Fold-Down)	(All Sizes)	5000# (Pair)
Patriot Ramps (Fold-Down)	(All Sizes)	4000# (Pair)
Patriot Ramps 14K (Fold-Down)	(All Sizes)	5000# (Pair)
Dump Trailers (Side-Stow, Optional)	(All Sizes)	4000# (Pair)
ATV (83-Wide, Side-Stow)	(All Sizes)	1200# (Pair)
ATV (88-Wide, Side-Stow)	(All Sizes)	750# (Pair)
Open Motorcycle (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down, Bi-Fold)	PU-SLINGSHOT	1500#
Open Car Hauler 2.0 (Stow)	(All Sizes)	4000# (Pair)
Open Car Hauler 2.0-10K (Stow)	(All Sizes)	4000# (Pair)
Open Car Hauler Standard (Stow)	(All Sizes)	4000# (Pair)
Open Snow (Rear-Stow)	PFS	750#
Sport Deck (Rear-Stow, Telescoping)	PSD	1000#
Enclosed Cargo (4, 5, 6-Wide)	(All Sizes)	1500#
Enclosed Cargo (7, 7.5-Wide)	(All Sizes)	1500#
Enclosed Cargo (8.5-Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle (7-Wide)	(All Sizes)	1500#
Enclosed Car Hauler (8.5-Wide)	(All Sizes)	4000#
Enclosed Gooseneck (8.5-Wide, Rear)	(All Sizes)	4000#
Enclosed Gooseneck (8.5-Wide, Side, Optional)	(All Sizes)	1200#
Enclosed Snowmobile (7, 7.5, 101-Wide, Rear)	(All Sizes)	1500#
Enclosed Snowmobile (7, 7.5, 101-Wide, Front)	(All Sizes)	1200#
Enclosed Snowmobile (Crossover, Rear)	(All Sizes)	1500#