OPEN SLINGSHOT TRAILERS

6.5'x14'



STANDARD FEATURES

- > All-Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > 3500# Wishbone Style Coupler w/2" Ball
- > (2) 5000# Safety Chains
- > Torsion Axles
- > Bolt On Fenders
- > Extruded Aluminum Decking



- > 7' Fold Down Bi-Fold Rear Ramp
- > Recessed Rubber Mounted LED Lights
- > Beavertail
- > Front Bumper

- > (4) HD D-Rings
- > 4-Way Flat Power Connection
- > Limited 4-Year Warranty

STANDARD SPECIFICATIONS

Trailer Model	Slingshot 6.5x14			
Model Number	PU6.5x14SLINGSH0T			
Deck (WxL)	80"x168"			
Overall (WxL)	102"x18'			
Deck Height	20"			
Hitch Height	16"			
Decking	Extruded Aluminum			
Heavy Duty D-Rings	4			
Axle(s) - Qty/Rating	1-3500#			
Wheels	15" Aluminum			
Tires	205/75R15			
GVWR	2990#			
Curb Weight	TBD			
Payload	TBD			
Wheel Jack	1200#			

OPTIONS & ACCESSORIES (Expanded list of available options can be found in MES option Section)

ACCESSORIES		TIRE/WHEEL ASSEMBLIES & ACCESSORIES
Large, Lockable Tongue-Mounted Diamond Plate Toolbox (Requires Wishbone Tongue)		Bolt-On Spare Tire Carrier (Tongue-Mounted)

