OPEN TILTING CAR HAULER TRAILERS

8'x20' - 8'x24'

PERIONAL TRAILERS



STANDARD FEATURES

- > All-Aluminum Construction
- > 16" 0/C Crossmembers
- > 2"x6" Subframe Tubing (Outer & Tongue)
- > 12500# Coupler w/2-5/16" Ball
- > 6" Front Bumper
- > 5000# Wheel Jack
- > Torsion Ride Axles
- > Extruded Aluminum Decking

- 8'x20' 8'x24'
- > (4) 5000# Recessed D-Rings
- > 7-Way Round Power Connection
- > Removable Aluminum Fender (D/S)
- > Hydraulic Tilt System w/Control Valve
- > 18" Stationary Front Deck
- > Recessed Rubber Mounted LED Lights
- > (2) 15000# Safety Chains
- > Limited Lifetime Warranty

STANDARD SPECIFICATIONS

| Trailer Model | Open Car Aluminum Deck 20' Tilt | Open Car Aluminum Deck 22' Tilt | Open Car Aluminum Deck 24' Tilt |
|----------------------|---------------------------------|---------------------------------|---------------------------------|
| Model Number | POCH8x20TILT | POCH8x22TILT | POCH8x24TILT |
| Deck (WxL) | 80"x20' | 80"x22' | 80"x24' |
| Overall (WxL) | 101"x24'4" | 101"x26'4" | 101"x28'4" |
| Deck Height | 23" | 23" | 24" |
| Hitch Height | 18" | 18" | 19" |
| Decking | Extruded Aluminum | Extruded Aluminum | Extruded Aluminum |
| 5000# D-Rings | 4 | 4 | 4 |
| Axle(s) - Qty/Rating | 2-3500# | 2-3500# | 2-5200# |
| Wheels | 15" Aluminum | 15" Aluminum | 15" Aluminum |
| Tires | 205/75R15 | 205/75R15 | 225/75R15 |
| GVWR | 7250# | 7250# | 9990# |
| Curb Weight | 1895# | TBD | TBD |
| Payload | 5355# | TBD | TBD |

OPTIONS & ACCESSORIES (Expanded list of available options can be found in MES option Section)

| CONSTRUCTION OPTIONS | TIRE/WHEEL ASSEMBLIES & ACCESSORIES | |
|---|--|--|
| Upgrade to Removable Curbside Fender | Spare 14" Aluminum Wheel w/ 205/75R14 Tire | |
| Integrated Heavy Duty Tire Rack | Spare 15" Silver Mod Wheel w/ 205/75R15 Tire | |
| ACCESSORIES | Spare 15" Aluminum Wheel w/ 205/75R15 Tire | |
| Air Dam for Open Car Hauler | Spare 15" Aluminum Wheel w/ 225/75R15 Tire (6-Lug) | |
| Large, Lockable Tongue-Mounted Diamond Plate Toolbox (Requires Wishbone Tongue) | Bolt-On Spare Tire Carrier (Tongue-Mounted) | |
| AXLE OPTIONS | TIE DOWN OPTIONS | |
| Upgrade to 2-5K Torsion Braked Axles (From 2-3K Braked; (OCH/HD Utility) | 5000# Recessed Heavy Duty D-Ring w/Backing Plate (Installed) | |
| | Light Duty Surface-Mounted D-Ring (Installed) | |

